

PM80

SMART BEYOND RUGGED ENTERPRISE MOBILITY

Powerful Qualcomm Snapdragon will free your work

Qualcomm's Snapdragon MSM8916 processor is a market-proven AP(Application Processor) which has Quad-Core with 1.2GHz clock speed. It is truly SoC(System on a Chip) having 4G LTE, Wireless LAN, Bluetooth, S-GPS and Camera bus interface.

Google Android 6.0.1

PM80 runs on Google's latest Android 6.0.1 Marshmallow Operating System and it is certified by Google Mobile Services (GMS) to support all Google official API including Google Play.

Wider & Brighter IPS display provides better visibility

PM80 adopts 5.0" IPS panel TFT-LCD with capacitive touch screen and it supports wide-viewing angle and dayllight redability in order to maximize the best performance in the out-field. To support harsh environment, top of screen is protected Corning Gorilla Glass 3 for maximum durability.

Frequently using 4 "HARD" keys towards field-work-forces

Most of Enterprise EDA in the market adopts capacitive-based touch button even for the most frequently used Recent App, Home, Back button. Not every user prefer to use Stylus pen in the field, PM80 features with 4 hard keys: Home, Menu, Back button and plus user-programmable / assignable key, which is very essential forious field applications.



Powerful Wireless; 4G LTE & IEEE 802.11 a/b/g/n and versatile data-input funtions


As of Enterprise mobility purposes, PM80 is completely tuned for Enterprise work-forces; smooth hand-over between WWAN and WLAN each other, seamless roaming among many routers & access points in the harsh working environment, because Enterprise users prior seamless connectivity to speed































PM80

PHYSICAL CHARACTERISTICS

Dimensions

With MSR 156mm L x 82mm W x 22mm D

 $6.1 in \ L\,x \ 3.2 in \ W\,x \ 0.9 \ in \ D$

Without MSR $156mm\ L\ x\ 82mm\ W\ x\ 21mm\ D$

6.1 in. Lx 3.2 in. W x 0.8 in D

Weight

With MSR 293g / 10oz Without MSR 279g / 9.8oz

5.0", IPS panel (720 x 1280 pixel) HD Display

Corning Gorilla Glass

Daylight readable (500 nits typical)

Wideviewing angle Capacitive touch Anti-raindrop

Power

Standard Battery 3,000mAh Li-ion rechargeable Extended Battery 4,000mAh Li-ion rechargeable

Keypad 4 physical keys

(Recent Apps, Home, Back &

Programmable)

Supports VoIP Audio Support

Two built-in microphones (Noise-cancelling)

Speaker

Receiver and headset jack (3.5mm) Wireless Bluetooth headset support

Standard

Communications either cradle or USB direct sync cable

Full speed USB 2.0 from

Notification

2 x dual color LEDs

for Power, Warning, & Scan reading

Scan Alert Vibration

PERFORMANCE CHARACTERISTICS

Main-Processor

Oualcomm MSM8916 @ 1.2GHz Ouad-core

Operating System

Google Android 6.0.1 Marshmallow

(CTS & GMS is certified)

Windows 10 IoTEnterprise Mobile

Memory and Storage

RAM ROM 16GB NAND Flash Slot

Micro-SD Micro-SD card slot supports

up to 32GB SDHC

Sensor Gyroscope, Accelerometer, Light Sensor

Proximity Sensor

USER ENVIRONMENT

Operating -20°C to 60°C / -4°F to 140°F Temperature

Storage

-25°C to 70°C / -13°F to 158°F

Temperature

Humidity 95% Non-condensing Drop MIL-STD 810G for 1.2m (4ft) over the

operating temperature

Water/Dust Proof IP67

Tumble 250cvcle (500hits) at 1m / 3.3ft

±15 kV air discharge Electrostatio Discharge ±8 kV contact discharge

DATA CAPTURE

Camera

Rear 8.0MP with LED flash

Front 2.0MP

Magnetic Stripe Reader (Optional)

3 track MSR with water proof sealed ANSI / ISO7813 standard, Encrypted

GLOBAL POSITIONING SYSTEM

GPS

12 channel integrated GPS: assisted via WAN carrier: accuracy within 3m, Stand-alone GPS available, support GLONASS

WIRELESS

Wireless WAN

EDGE/GPRS/GSM 850/900/1800/1900

850/900/1900/1700/2100 MHz WCDMA FDD2, FDD3, FDD4, FDD5, FDD13, FDD17 LTE

Wireless LAN

IEEE 802.11a/b/g/n/d/h/i/k/r/v, Radio

IPv4, IPv6, 1X1 SISO

Data Rates IEEE 802.11a/n: Up to 150 Mbps;

IEEE 802.11b/g/n: Up to 72.2 Mbps

Operating 1 to 13 (2412~2472MHz). Channels 36 to 165 (5180~5825MHz)

20, 40 MHz Channel

Bandwidth

Security and WEP(40 or 104bit), WPA/WPA2 Personal (TKIP, AES); WPA/WPA2 Enterprise (TKIP/AES) - PEAP(MSCHAPv2, GTC). Encryption

TLS, TTLS(PAP, MSCHAP, MSCHAPv2, GTC), PWD. SIM. AKA. AKA

FAST(MSCHAPv2, GTC), LEAP

Fast Roam PMKID Caching: Cisco CCKM, 802.11r

Wireless PAN

Bluetooth Integrated Bluetooth Class Il, Ver. 4.0

0 to 78 (2402-2480MHz) Channels

Data Rates 1, 2, 3Mbps

REGULATORY APPROVALS AND COMPLIANCE

Certified CE & GCF, FCC & PTCRB (GCF test report), IC, ANATEL CCC & SRRC & NAL ,KC, TELEC & JATE, CB,RCM Environmental: RoHS II & WEEE compliant

ENTERPRISE SOLUTION

SOTI, Airwatch, Teamviewer



Power Launcher Kiosk mode with system restriction

Allows admin to restrict operator's access to system settings, MTP connection and screen capture

Direct Clone Master PDA becomes a local server for

a nearby Point Mobile device to automatically communicate and download/restore backup files

Scan2Set Unique two-step feature for Point

Mobile Android models that enables the fastest device deployment right out of

the box

ACCESSORIES

Standard Accessories



Standard Battery



LCD Protection Film

Wrist Landyard





Extended Battery







Vehicle Mount Cigar Jack Charger

B-9F Kabul Great Valley, 32, Digital-Ro 9 Gil, Geumcheon-Gu, Seoul, Korea 08512 www.pointmobile.co.kr T+82 2 3397 7870~1 F+82 2 3397 7872 *lobile*