

sewoo

HIGH SPEED DESKTOP THERMAL POS PRINTER

SLK-T21EBII



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Printing notice accessory : Melody box
- Wall mount installation available



Rugged Design



Barcode



Durable

50~82.5MM

Paper width



Paper Sensor



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



Various interface

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 8.6ips(220mm/sec)

Print Width

Up to 2.8" (72mm)

Resolution

Standard: 180dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper End, Paper Low,

Cover Open

Option : Black Mark

Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 1.8 Million cuts

Drawer port

2 circuits(24V, 1A Max.)

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

5.98" x 8.03" x 5.82"
(152 x 204 x 155mm)

Weight

3.74lb(1.7Kg)

INTERFACES

Standard

USB(B type)+

Serial(RS-232C_9pin)+

Ethernet Built-in

CERTIFICATIONS

CE, FCC, KC, UL/cUL,
ENERGY STAR

OPERATING CHARACTERISTICS

Operating Temperature

32 ~ 113°F(0 ~ 45°C)

Operating Humidity

35 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%

MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Linerless(Optional)

Media Width

1.9~3.2"(50mm ~82.5mm)

Media Core Diameter

0.4"(12.5mm ± 0.5mm)

Media Roll Diameter

3.1"(ø 80mm)

Thickness

0.06~0.09mm

SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(2012, 8, 7, 2008, VISTA,

2003, XP, 32bit & 64bit), Windows CE &

Mobile Driver (CE 4.2 ~, Mobile 5.0 ~),

Linux Driver, Mac Driver, OPOS Driver,

JavaPOS Driver, iOS SDK, Android(2.1 ~)

SDK, Windows SDK, Windows CE SDK

Linux SDK, Xamarin SDK, Cordova Plugin

BARCODES

1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX

FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic

ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_Sales@miniprnter.com

Germany Office

Edewecht, Deutschland

T. +49-4405-989-0-838

E. europe@miniprnter.com

China Office

SHANG HAI SHI, SONG JIANG QU

T. +86-177-1729-9100

E. sales@miniprnter.com

México

Cuauhtémoc, Mexico

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. sales@miniprnter.com

